

BioTassu is a grapple tilt to large and small machines. With BioTassu grapple can be tilted up which reduces the need for space between the trees. BioTassu works with the base machine's hydraulics.

The forwarder's performance is increased and saves time and money.

- BioTassu is an equipment which is simple to assemble.
- With the new radio control requires no additional hydraulic, only grapple open and grapple close.
- You select the function with the optional keypad mounted on the left joystick.
- Two batteries and charger included.
- BioTassu reduce impact shock to the machine and operator.
- The budle is simply out of the trees.
- BioTassu minimizes damage to remaining trees.

Benefits

- BioTassu simplifies and makes the work more quickly when thinning
- Reduces the impact shock to the machine and driver
- The forwarder's performance is increased
- Saves time
- Greater profitability
- Minor damage to the remaining trees




Application areas

- Forestry
- On timber cranes
- Clearing of electricity lines

MODEL S35

- CE-marked
- Weight about 60kg
- MAX load 3500kg
- All grapples 0 -0,28m³
- Suitable for light and medium heavy forestry machinery.
- Suitable for all forwarder's.
- Can be mounted on all most commonly used grapples.

| MODEL | | BS35 | |
|-----------------------------|------------------------|-------|-------|
| A | WIDTH | mm | 418 |
| B | HEIGHT WHEN CLOSED | mm | 380 |
| C | LENGHT | mm | 495 |
| D | HEIGHT ROTATOR-GRAPPLE | mm | 215 |
| E | MAX HEIGHT | mm | 545 |
| WEIGHT | | kg | 62 |
| MAX LOAD | | kg | 3500 |
| MAX WORKING PRESSURE | | Bar | 210 |
| OIL FLOW | | l/min | 20-60 |
| MOVING TIME UP 20L/MIN | | s | 2 |
| MOVING TIME DOWN 20L/MIN | | s | 1 |
| CONNECTION ROTATOR-BIOTASSU | | C | |
| CONNECTION BIOTASSU-GRAPPLE | | C | |
| ORDER CODE | | BS35 | |



* Note! The manufacturer reserves the right to make changes in technical specifications.

