

**Unique log grapple with tilt function**

- Developed to make logging more efficient.  
 The T220 tilt grapple is a normal loading grapple with built-in tilt function, but still works with the same hydraulics as a traditional loading grapple. You only need 2 hydraulic lines (grapple open/close).  
 The tilt function is controlled wirelessly. Two extra control buttons/pedals (tilt up/tilt down) are included in the delivery. These control buttons can be installed in a suitable place. 2 batteries and a battery charger are also included in the delivery.



**FEATURES**

Fast and easy to use - increases productivity  
 Stable both in felling and loading position  
 Easy to install  
 No additional hydraulic lines are needed - only grapple open and grapple close  
 Completely stepless control - for example, stop the tilt half way if necessary

**Control system alternatives**

Standard: 1 double-acting hydraulic line, grapple open/close + Remote control for tilt function

**Grapple claw alternatives**

Standard: Traditional log grapple claws (closed ends)

Option: Energy grapple claws (open ended)

Option: A-model claws (with diagonal plates)

**Technical information**

Model	T220 <i>G2</i>
Grapple size	0,22 m2
Weight	155 kg
Rec. working pressure	200-230 bar
Rec. oil flow rate	30 - 50 l/min.
Opening of grapple	1200 mm
Attachment standard	173/6