

## BIOJACK® 180



√ Small forwarders, trailers, trucks, excavators 4-8 t ✓ Light and strong ✓ Quick cut, Ø17-20 cm √ Low stump





The **Biojack 180** is a robust and agile grapple designed for tough conditions. Easy and quick to install on the rotator of a crane. Its user-friendliness is what makes it special. It moves smoothly through the trees, and thanks to its diverse functions, it can be used both for cutting and loading, without any modification. The grapple can be used for **delimbing** trees, as standard.

Work cycle: Press the hydraulic command, the grapple grabs a tree, the knife cuts, the tilt fells the tree. Then use the grapple for sorting and loading duty, just like

Biojack grapples are durable and sturdy, manufactured by Nummek in Finland, from top quality materials. All our products are user-friendly, easy and fast to use instinctively, and can be customized according to your needs, so you can simply focus on your work.

	Weight	<b>CRANE</b> 200 kg (440 lbs)	EXCAVATOR 240 kg (530 lbs)
	Cut diameter max. (hardwood- softwood)	170-200 mm (7-8")	170-200 mm (7-8")
	Cut mode	Blade Hardox 500	Blade Hardox 500
	Oil flow	35-60 L/min (9-16 gpm)	35-60 L/min (9-16 gpm)
	Operating pressure	180-220 bar	180-220 bar
	Back pressure max	20-30 bar	20-30 bar
	<b>Grapple opening</b>	775 mm (30")	775 mm (30")
	Grapple type	Delimbing grapple standard	Delimbing grapple standard
	Shut off valves	Blade Tilt	Boom: No BA90: Blade
	Height in felling position	470 mm (18")	470 mm (18")
 	Connection to rotator	Flange ø173 mm	Boom or BA90
	Hydraulic connections	3/8" (2 hoses, pressure and return)	3/8" (2 hoses, pressure and return)
	Base machines	Tractors, trucks, forwarders	Excavators 4-8 t, telehandlers
	Options	Rotator adapter Normal grapple (round wood) 4-fingered grapple	Boom BA90 Rotator CPR9 Coupling Box Normal grapple (round wood) 4-fingered grapple

