

## BIOJACK® 230



√ Forwarders, trailers, trucks, excavators 6-10 t ✓ Light and strong √ Quick cut, Ø20-25 cm √ Low stump





The **Biojack 230** is a robust and agile grapple designed for tough conditions. Easy and quick to install on the rotator of a crane. Its user-friendliness is what makes it special. It moves smoothly through the trees, and thanks to its diverse functions, it can be used both for **cutting** and **loading**, without any modification. The grapple can be used for **delimbing** trees, as standard.

**Work cycle**: Press the hydraulic command, the grapple grabs a tree, the knife cuts, the tilt fells the tree. Then use the grapple for sorting and loading duty, just like that!

Biojack grapples are durable and sturdy, manufactured by Nummek in Finland, from top quality materials. All our products are user-friendly, easy and fast to use instinctively, and can be customized according to your needs, so you can simply focus on your work.

	Weight	<b>CRANE</b> 230 kg (505 lbs)	EXCAVATOR 270 kg (595 lbs)
	Cut diameter max. (hardwood- softwood)	200-250 mm (8-10")	200-250 mm (8-10")
ł	Cut mode	Blade Hardox 500	Blade Hardox 500
ē,	Oil flow	40-80 L/min (10-21 gpm)	40-80 L/min (10-21 gpm)
ł	Operating pressure	190-240 bar	190-240 bar
_	Back pressure max	20-30 bar	20-30 bar
2	<b>Grapple opening</b>	775 mm (30")	775 mm (30")
	Grapple type	Delimbing grapple standard	Delimbing grapple standard
J Š	Shut off valves	Blade Tilt	Boom: No BA90: Blade
ā	Height in felling position	490 mm (19")	490 mm (19")
ł	Connection to rotator	Flange ø173 mm	Boom or BA90
	Hydraulic connections	1/2" (2 hoses, pressure and return)	1/2" (2 hoses, pressure and return)
	Base machines	Tractors, trucks, forwarders	Excavators 6-10 t, telehandlers
	Ontions	Rotator adapter Normal grapple (round wood)	Boom BA90 Rotator CPR9 Coupling Box Normal grapple (round wood)

