





- √ Excavators 10-20 t
  - **✓** Robust structure
- ✓ Quick cut, Ø35-45 cm
  - √ Low stump



Biojack Oy | www.biojack.fi Valimotie 1, Fl-25500 Perniö | info@biojack.fi



The **Biojack 450** is a heavy and robust grapple designed for tough conditions. The grapple holds the tree firmly before the cut starts, max safety next to powerlines. Its user-friendliness is what makes it special. It moves smoothly through the trees, and thanks to its diverse functions, it can be used both for **cutting** and **loading**, without any modification. Available with the **accumulation** grapple (E-kit), the upper secondary grapple (EG-kit), which can be used for **delimbing** or moving trees vertically after cut, as well as rotator options.

**Work cycle**: Press the hydraulic command, the grapple grabs a tree, the knife cuts, the tilt fells the tree. Then use the grapple for sorting and loading duty, just like that!

Biojack grapples are durable and sturdy, manufactured by Nummek in Finland, from top quality materials. All our products are user-friendly, easy and fast to use instinctively, and can be customized according to your needs, so you can simply focus on your work.

**TECHNICAL DATA** Weight Biojack 450 550 kg (1220 lbs) Weight Biojack 450EG 710 kg (1565 lbs) Cut diameter max. 350-450 mm (hardwood-(14-17")softwood) **Cut mode** Blade Hardox 500 100-150 L/min Oil flow (26-40 gpm) **Operating pressure** 250-300 bar **Back pressure max** 30 bar **Grapple opening** 850 mm (33") **Grapple type** Round wood grapple Shut off valves Height in felling Bj450: 710 mm (28") Bj450EG: 1350 mm (53") position Coupling mode Hydraulic 3/4" (2 hoses, pressure and connections return) Excavators 10-20 t, **Base machines** telehandlers Rotator CPR15 Rotator TD Coupling Box E-kit, accumulation grapple **Options** Wireless control for the E-kit EG-kit, upper delimbing grapple Quick coupling

